



PRODUCT CATALOGUE



REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
HDCVI CAMERAS			
BULLET CAMERAS			
HCDA201	HAC-HFW1100RP-0360B-S3	Dahua HDCVI 1MP 720p Bullet IR 3.6mm 1/2.9" 1Megapixel CMOS 25/30fps@720P - High speed, long distance real-time transmission - Day/Night(ICR), AWB, AGC, BLC, 2D-DNR 3.6mm fixed lens - Max. IR LEDs length 20m, Smart IR - IP66, DC12V	
HCDA205-1	HAC-HFW1200SP-0360B	Dahua HDCVI 2MP 1080P Bullet IR 3.6mm 1/2.7" 2Megapixel CMOS - Max 30fps@1080P - HD and SD output switchable 3.6mm fixed lens - Max. IR length 30m, Smart IR - IP67, DC12V	
HCDA205-2	HAC-HFW1200SP-0360B-S3	Dahua HDCVI 2MP 1080P Bullet IR 3.6mm S3 1/2.7" 2Megapixel CMOS - Max 30fps@1080P - HD and SD output switchable 3.6mm fixed lens - Max. IR length 30m, Smart IR - IP67, DC12V	
HCDA206	DH-HAC-HFW1100RP-VF-S2	Dahua HDCVI 1MP 720p Bullet IR VF 1/2.9" 1Megapixel CMOS 25/30fps@720P - High speed, long distance real-time transmission - Day/Night(ICR), AWB, AGC, BLC, 2D-DNR 2.7~12mm vari-focal lens - Max. IR LEDs length 30m, Smart IR - IP66, DC12V	
HCDA206-2	DH-HAC-HFW1100RP-VF-S3	Dahua HDCVI 1MP 720p Bullet IR VF S3 1/2.9" 1Megapixel CMOS - Max 30fps@720P - HD and SD output switchable 2.7-12mm vari-focal lens - Max. IR length 30m, Smart IR - IP67, DC12V	
HCDA206-1	HAC-HFW1200RP-VF-IRE6	Dahua HDCVI 2MP 1080p Bullet IR VF 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P - High speed, long distance real-time transmission - HD and SD switchable - OSD Menu, control over coaxial cable - DWDR, Day/Night(ICR), AWB, AGC, BLC, 2DNR 2.7~12mm vari-focal lens - Max. IR LEDs length 60m, Smart IR - IP67, DC12V	
DOME CAMERAS			
HCDA301	HAC-HDW1100RP-0360B-S3	Dahua HDCVI 1MP 720p Dome IR 3.6mm 1/2.9" 1Megapixel CMOS 25/30fps@720P - High speed, long distance real-time transmission - Day/Night(ICR), AWB, AGC, BLC 3.6mm fixed lens - Max. IR LEDs length 20m, Smart IR - DC12V	
HCDA303-1	HAC-HDW1200MP-0360B	Dahua HDCVI 2MP 1080p Dome IR 3.6mm 1/2.7" 2Megapixel CMOS 25/30fps@1080P, 25/30/50/60fps@720P - High speed, long distance real-time transmission - HD and SD switchable - OSD Menu, control over coaxial cable - DWDR, Day/Night(ICR), AWB, AGC, BLC, 2DNR 3.6mm fixed lens - Max. IR LEDs length 30m, Smart IR - IP67, DC12V	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
HCDA303-2	HAC-HDW1200MP-0360B-S3	Dahua HDCVI 2MP 1080p Dome IR 3.6mm S3 • 1/2.7" 2Megapixel CMOS • Max 30fps@1080P • HD and SD output switchable • 3.6mm fixed lens • Max. IR length 30m, Smart IR • IP67, DC12V	
HCDA304-2	HAC-HDBW1100RP-VF-S2	Dahua HDCVI 1MP 720p Dome IR VF • 1/2.9" 1Megapixel CMOS • 25/30fps@720P • High speed, long distance real-time transmission • Day/Night vari-focal lens • Max. IR LEDs length 30m, Smart IR • IP66, IK10, DC12V	
HCDA304-4	HAC-HDBW1100RP-VF-S3	Dahua HDCVI 1MP 720p Dome IR VF S3 • 1/2.9" 1Megapixel CMOS • 25/30fps@720P • High speed, long distance real-time transmission • Day/Night(ICR), AWB, AGC, BLC, 2D-DNR • 2.7~12mm vari-focal lens • Max. IR LEDs length 30m, Smart IR • IP66, IK10, DC12V	
HCDA304-1	HAC-HDBW1200RP-VF	Dahua HDCVI 2MP 1080p Dome IR VF • 1/2.9" 1Megapixel CMOS • 25/30fps@720P • High speed, long distance real-time transmission • Day/Night(ICR), AWB, AGC, BLC, 2D-DNR • 2.7~12mm vari-focal lens • Max. IR LEDs length 30m, Smart IR • IP66, IK10, DC12V	
HCDA304-3	DH-HAC-HDBW1200RP-VF-2712-S3	Dahua HDCVI 2MP 1080p Dome IR VF S3 • 1/2.7" 2Megapixel CMOS • Max 30fps@1080P • HD and SD output switchable • 2.7-12mm vari-focal lens • Max. IR length 30m, Smart IR • IP67, IK10, DC12V	
PTZ			
HCDA402	DH-SD42212I-HC	Dahua HDCVI 2MP 1080p PTZ 12X • 1/2.8" 2Megapixel Exmor CMOS • Powerful 12x optical zoom • Max. 25/30fps@1080P • DWDR, 3D DNR • IP66, IK10	
HCDA403	DH-SD6C225I-HC	Dahua HDCVI 2MP 1080p PTZ IR 25X • 2Megapixel STARVIS™ CMOS • Powerful 25x optical zoom • Starlight technology • 120dB true WDR, 3D DNR • Max. 25/30fps@1080P, 25/30/50/60fps@720P • IR distance up to 150m • IP66	
HDCVI DVRs			
HCVR 4 Channel			
RCDA408-1	HCVR4104C-S3	Dahua HDCVI 4 ch 720p Lite slimline DVR S3 • Embedded processor • H.264 video compression • Max 5 channels (1 IP camera input) • Max 20 Mbps Incoming Bandwidth • Long distance over coax cable • Support 1 SATA HDD, up to 6TB	
RCDA400-10	HCVR5104HS-S3	Dahua HDCVI 4 ch 1080p Lite Pro 1U DVR S3 • Support HDCVI/Analog/IP Video input • H.264+/H.264 dual-stream video compression • All channel 1080N/720P realtime or 1080P non-realtime recording • HDMI/VGA simultaneous video output • 4 channel synchronous playback, GRID interface & smart search • Support 1 SATA HDD up to 6TB, 2 USB2.0 • Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & Smart Phone(DMSS)	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
RCDA418	HCVR7204A-S2	Dahua HDCVI 4 ch 1080p 1U DVR S2 - Support HDCVI/Analog/IP Video input - H.264 dual-stream video compression - All channel 1080P realtime recording 4 channel synchronous realtime playback, GRID interface & smart search - HDMI/VGA simultaneous video output - Support 2 SATA HDDs up to 8TB, 2 USB2.0 - ONVIF Version 2.4 conformance 3D intelligent positioning with Dahua PTZ dome camera - Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)	
RCDA419	HCVR7204A-V2	Dahua HDCVI 4 ch 1080p 1U DVR V2 - Support HDCVI/Analog/IP Video input - H.264 dual-stream video compression - All channel 1080P realtime recording 4 channel synchronous realtime playback, GRID interface & smart search - HDMI/VGA simultaneous video output - Support 2 SATA HDDs up to 8TB, 2 USB2.0 - ONVIF Version 2.4 conformance 3D intelligent positioning with Dahua PTZ dome camera - Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)	
HCVR 8 Channel			
RCDA412	HCVR4108C-S2	Dahua HDCVI DVR 8ch 720p Lite slimline DVR S2 - Support HDCVI & IP Video input - H.264 dual-stream video compression - All channel 720P recording - HDMI/VGA simultaneous video output 8 channel synchronous playback, GRID interface & smart search - ONVIF Version 2.4 conformance - Support 1 SATA HDD up to 4TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera - Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)	
RCDA416	DHI-HCVR4108C-S3	Dahua HDCVI DVR 8ch 720p Lite slimline DVR S3 - Support HDCVI/Analog/IP Video input - H.264 dual-stream video compression - All channel 720P recording - HDMI/VGA simultaneous video output 8 channel synchronous playback, GRID interface & smart search - ONVIF Version 2.4 conformance - Support 1 SATA HDD up to 6TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera - Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS)	
RCDA415	DHI-HCVR5108HS-S3	Dahua HDCVI DVR 8ch 720p Pro 1U DVR S3 - Support HDCVI/Analog/IP Video input - H.264+/H.264 dual-stream video compression - All channel 1080N/720P realtime or 1080P non-realtime recording - HDMI/VGA simultaneous video output 8 channel synchronous realtime playback, GRID interface & smart search - ONVIF Version 2.4.1 conformance - Support 1 SATA HDD up to 6TB, 2 USB2.0 3D intelligent positioning with Dahua PTZ dome camera - Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS)&Smart Phone(DMSS) - Advanced intelligent functions: Tripwire, Intrusion, Abandoned/Missing, Face Detection	
HCVR 16 Channel			
RCDA423	DHI-XVR4116HS-S3	Dahua HDCVI 16ch 720p Lite 1U XVR - Embedded processor - H.264 video compression - Support HDCVI/AHD/TVI/CVBS/IP video inputs - Max 18 channels (2 IP camera inputs) - Long transmission distance over coax cable - Support 1 SATA HDD, up to 6TB	
RCDA417-A	DHI-XVR5216AN	Dahua HDCVI 16ch 1080p Lite Pro 1U XVR - Embedded processor - H.264+/H.264 dual-stream video compression - Support HDCVI/AHD/TVI/CVBS/IP video inputs - Max 8 channels IP camera inputs - Max 96Mbps Incoming Bandwidth - Smart Search and Intelligent Video System	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
HCVR 32 Channel			
RCDA414-A	DHI-XVR5432L	Dahua HDVI 32ch 1080P Lite 1.5U XVR • Embedded processor • H.264+/H.264 dual-stream video compression • Support HDCVI/AHD/TVI/CVBS/IP video inputs • Max 16 channels IP camera inputs • Max 64Mbps Incoming Bandwidth • Smart Search and Intelligent Video System	
IP CAMERAS			
BULLET CAMERAS			
ICDA206-1	IPC-HFW1120SP-0360B	Dahua IP 1.3MP Bullet IR 3.6mm Lite • 1/3" 1.3Megapixel progressive CMOS • H.264+ & H.264 dual-stream encoding • 25/30fps@1.3M(1280×960) • DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 3.6 mm fixed lens • Max IR LEDs Length 30m • IP67, PoE	
ICDA205	IPC-HFW4300EP-0360B	Dahua IP 3MP Bullet IR 3.6mm ES • 1/3" 3Megapixel progressive CMOS • H.264+ & H.264 dual-stream encoding • Max 20fps@3.0M(2048×1536)&25/30fps@1080P(1920×1080) • DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 3.6 mm fixed lens • Max IR LEDs Length 30m • IP66, PoE	
ICDA220	IPC-HFW1320SP-0360B	Dahua IP 3MP Bullet IR 3.6mm Lite • 1/3" 3Megapixel progressive scan CMOS • H.264&MJPEG dual-stream encoding • Max 20fps@3M(2048×1536)&25/30fps@1080P(1920×1080) • DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 3.6mm fixed lens • Max. IR LEDs Length 20m • IP67, PoE	
ICDA229	IPC-HFW2120RP-VFS	Dahua IP 1.3MP Bullet IR VF Lite • 1/3" 1.3Megapixel progressive scan CMOS • H.264 & MJPEG dual-stream encoding • 25/30fps@1.3M(1280×960) • DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 2.7~12mm varifocal lens • Max IR LEDs Length 60m • IP67, PoE	
ICDA219-1	IPC-HFW2320RP-VFS	Dahua IP 3MP Bullet IR VF Lite • 1/3" 3Megapixel progressive CMOS • H.264 & MJPEG dual-stream encoding • Max 20fps@3M(2304×1296) (2048×1536) &25/30fps@1080P(1920×1080) • DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 2.7~12mm varifocal lens • Max IR LEDs Length 30m • IP67, PoE • Micro SD card slot, up to 128GB	
ICDA221	IPC-HFW4421EP-0360B	Dahua IP 4MP Bullet IR 3.6mm ES2 • 1/3" 4Megapixel progressive scan CMOS • H.264 & MJPEG triple-stream encoding • Smart Detection supported • Max 20fps@4M(2560×1440) & 25/30fps@3M(2304×1296) • WDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC • Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS • 3.6mm fixed lens (6mm optional) • Max. IR LEDs Length 40m • IP67, PoE	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
ICDA222	IPC-HFW5421EP-Z	Dahua IP 4MP Bullet IR MZ ES2 1/3" 4Megapixel progressive scan CMOS - H.264&MJPEG triple-stream encoding - Max 20fps@4Mp(2560×1440), 25/30fps@3Mp(2304×1296) - Smart Detection supported - WDR(120dB), Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7mm ~12mm motorized lens - Max. IR LEDs Length 50m - IP67, PoE - Micro SD card memory	
ICDA213-1	IPC-HFW8331EP-Z	Dahua IP 3MP Bullet IR MZ Ultra 1/2.8" 3Megapixel progressive scan CMOS - Support H.265/H.264/MJPEG codec - Smart triple streams supported - Max 25/30fps@3MP(2048×1536) - Ultra WDR up to 140dB - Ultra 3D DNR - Ultra Defog, ROI, EIS - Smart detection - Intelligent Function 2.8 ~12mm varifocal motorized lens - Max. IR LEDs length 50m - Micro SD memory, IP67, PoE	
IP DOME CAMERAS			
ICDA321	DH-IPC-HDW1120SP-0360B	Dahua IP 1.3MP Dome IR 3.6mm Lite 1/3" 1.3Megapixel progressive scan CMOS - H.264&MJPEG dual-stream encoding 25/30fps@1.3M(1280×960) - DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens - Max. IR LEDs Length 30m - IP67, PoE	
ICDA327	IPC-HDW1320SP-0360B	Dahua IP 3MP Dome IR 3.6mm Lite S 1/3" 3Megapixel progressive scan CMOS - H.264&MJPEG dual-stream encoding - Max 20fps@3M(2048×1536)&25/30fps@1080P(1920×1080) - DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens - Max. IR LEDs Length 30m - IP67, PoE	
ICDA321-1	IPC-HDBW1320EP-0360B	Dahua IP 3MP Dome IR 3.6mm Lite E 1/3" 3Megapixel progressive scan CMOS - H.264&MJPEG dual-stream encoding - Max 20fps@3M(2048×1536) (2304×1296)&25/30fps@1080P(1920×1080) - DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens - Max. IR LEDs Length 30m - IP67, IK10, PoE	
ICDA326-1	IPC-HDBW2120RP-VFS	Dahua IP 1.3MP Dome IR VF Lite 1/3" 1.3Megapixel progressive scan CMOS - H.264 & MJPEG dual-stream encoding 25/30fps@1.3M(1280×960) - DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7~12mm varifocal lens - Max IR LEDs Length 30m - IP67, IK10, PoE - Micro SD card slot, up to 128GB	
ICDA326-2	IPC-HDBW2320RP-VFS	Dahua IP 3MP Dome IR VF Lite 1/3" 3Megapixel progressive CMOS - H.264 & MJPEG dual-stream encoding - Max 20fps@3M(2304×1296) (2048×1536)&25/30fps@1080P(1920×1080) - DWDR, Day/Night(ICR), 3DNR, AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.7~12mm varifocal lens - Max IR LEDs Length 30m - IP67, IK10, PoE - Micro SD card slot, up to 128GB	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
ICDA308-1	IPC-HDBW4120EP-0360B	Dahua IP 1.3MP Dome IR 3.6mm ES2	
		1/3" 1.3Megapixel progressive scan CMOS - H.264&MJPEG triple-stream encoding 25/30fps@1.3Mp(1280×960) - DWDR, Day/Night(ICR), 3DNR,AWB,AGC,BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens (2.8mm, 6mm optional) - Max. IR LEDs Length 30m - IP67, IK10, PoE	
ICDA329-1	IPC-HDBW4421FP-0360B	Dahua IP 4MP Dome IR 3.6mm ES2	
		1/3" 4Megapixel progressive scan CMOS - Support H.264&MJPEG dual codec - Max 20fps@4M(2688×1520),25/30fps@3M(2304x1296) - Smart Detection supported - WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC, - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 3.6mm fixed lens - Max. IR LEDs Length 20m - IP67, IK10, PoE	
ICDA319-3	DH-IPC-HDBW4431EP-AS-0280B-S2	Dahua IP 4MP Dome IR 2.8mm ES3 Audio	
		1/3" 4Megapixel progressive scan CMOS - H.265&H.264 triple-stream encoding 25/30fps@4M(2688×1520) - Smart Detection supported - WDR(120dB), Day/Night(ICR), 3DNR,AWB,AGC,BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS 2.8mm fixed lens 1/1 Alarm in/out, 1/1 audio in/out - Max. IR LEDs Length 30m - Micro SD memory, IP67, IK10, PoE	
ICDA304-1	IPC-HDBW8331EP-Z	Dahua IP 3MP Dome IR MZ Ultra	
		1/2.8" 3Megapixel progressive scan CMOS - Support H.265/H.264/MJPEG dual codec - Smart triple streams supported - Max 25/30fps@3MP(2048x1536) - Ultra WDR up to 140dB - Ultra 3D DNR - Ultra Defog, ROI, EIS - Smart detection - Intelligent Function 2.8 ~12mm varifocal motorized lens - Max. IR LEDs length 50m - Micro SD memory, IP66, IK10, PoE,	
IP PTZ CAMERAS			
ICDA410-1	DH-SD22204T-GN	Dahua IP 2MP PTZ 4X	
		1/2.7" 2Megapixel CMOS - Powerful 4x optical zoom - Support Triple-streams encoding - WDR, Day/Night(ICR), Ultra DNR - Max. 25/30fps@1080P, 25/30/50/60fps@720P - IVS(Optional) - Support PoE, Wifi - Max 100°/s pan speed - IP66, IK10	
ICDA403-1	DH-SD6C230T-HN	Dahua IP 2MP PTZ 100m IR 30X	
		30x optical zoom - Support Triple-streams encoding - DWDR, Day/Night(ICR), Ultra DNR, Auto iris, Auto focus - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS - Max 240°/s pan speed, 360° endless pan rotation - Up to 300 presets, 5 auto scan, 8 tour, 5 pattern - Built-in 2/1 alarm in/out - Support intelligent 3D positioning with DH-SD protocol - Micro SD memory, IP66 - IR Distance up to 100m	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
ICDA408-1	SD6AE230F-HNI	Dahua IP 2MP PTZ 200m IR 30X Ultra Starlight - Powerful 30x optical zoom - Ultra-low light star-light camera - H.264 & MJPEG Three-stream encoding - Max 60fps@720P and 30fps@1080P resolution - Defog, WDR, EIS, ROI, Day/Night(ICR), DNR (2D&3D), Auto iris, Auto focus, AWB, AGC,BLC - Auto-tracking and IVS - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS - Max 240°/s pan speed, 360° endless pan rotation - Up to 300 presets, 5 auto scan, 8 tour, 5 pattern - Built-in 7/2 alarm in/out - Support intelligent 3D positioning with DH-SD protocol - Micro SD memory, IP67, IK10, Hi-POE - IR Distance up to 200m	
IP PINHOLE CAMERAS			
ICDA700	DH-HUM8101P-R	Dahua IP 1.3MP Pinhole 3.6mm Round 1/3" 1.3Megapixel progressive scan CMOS - H.264 & MJPEG dual-stream encoding - Max 25/30fps@1.3MP (1280\960) - Day/Night(Electronic), 3DNR, AWB,AGC,BLC - Smart detection 3.6mm fixed lens - Micro SD memory, PoE	
ICDA701	DH-HUM8101P-S	Dahua IP 1.3MP Pinhole 3.6mm Square 1/3" 1.3Megapixel progressive scan CMOS - H.264 & MJPEG dual-stream encoding - Max 25/30fps@1.3MP (1280\960) - Day/Night(Electronic), 3DNR, AWB,AGC,BLC - Smart detection 3.6mm fixed lens - Micro SD memory, PoE	
IP FISHEYE CAMERAS			
ICDA900	IPC-EBW8600P	Dahua IP 6MP Fisheye IR 1.55mm 1/1.8" 6Megapixel progressive scan CMOS - H.264 & MJPEG dual-stream encoding - Max 25/30fps@6.0M(3072x2048) - Multiple De-wrap Mode: Original ,Panoramic, Double Panoramic,1+3,Eptz,4 pictures - DWDR, Day/Night(ICR), 3DNR,ROI,AWB, AGC, BLC - Multiple network monitoring: Web viewer, CMS(DSS/PSS) & DMSS - Max.IR LEDs Length 10m 1/1 Audio in/out(Built in Mic) - Micro SD memory,IP67,IK10,PoE	
NVRS			
NVR 8 Channel			
RCDA311	NVR1108H-P	Dahua IP 8ch 4 PoE Mini 1U NVR - Up to 8 channel with 1080P realtime live view - Dual codec decoding - Max 56Mbps incoming bandwidth - HDMI/VGA simultaneous video output - All channel synchronous realtime playback, GRID interface& smart search - ONVIF Version 2.3 conformance 3D intelligent positioning with Dahua PTZ camera - Support 1 SATA HDD up to 4TB, 2 USB2.0 - Support IPC UPnP, 4PoE ports - Support P2P, QR code - Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & Smart Phone(DMSS)	
RCDA321	NVR1108-P	Dahua IP 8ch 4 PoE Slimline Mini 1U NVR - Up to 8 channel IP camera input - H.264/MJPEG dual codec decoding - Max 56Mbps incoming bandwidth - HDMI/VGA simultaneous video output - All channel synchronous realtime playback, GRID interface - ONVIF Version 2.3 conformance 3D intelligent positioning with Dahua PTZ camera - Support 1 SATA HDD up to 4TB, 2 USB2.0 - Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & Smart Phone(DMSS) - Support IPC UPnP, 4PoE ports - Support P2P, QR code	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
RCDA317	NVR4208-8P	Dahua IP 8ch 8 PoE 1U Lite NVR • H.264+/H.264 codec decoding • Max 200Mbps Incoming Bandwidth • Up to 5MP Resolution for Preview and Playback • HDMI/VGA simultaneous video output • Support IPC UPnP, 8PoE ports • Support ANR technology to enhance the storage reliability when the network break down	
RCDA317-A	NVR4208-8P-4KS2	Dahua 8 Channel 1U 8PoE 4K&H.265 Lite Network Video Recorder • H.265/H.264 codec decoding • Max 200Mbps Incoming Bandwidth • Up to 8MP Resolution for Preview and Playback • HDMI/VGA simultaneous video output • Support IPC UPnP, 8PoE ports • Support ANR technology to enhance the storage reliability when the network break down	
NVR 16 Channel			
RCDA318-A	NVR4216-16P-4KS2	Dahua IP 16ch 16 PoE 1U Lite NVR 4K • H.265/H.264 codec decoding • Max 200Mbps Incoming Bandwidth • Up to 8MP Resolution for Preview and Playback • HDMI/VGA simultaneous video output • Support IPC UPnP, 16PoE ports • Support ANR technology to enhance the storage reliability when the network break down	
RCDA318	NVR4416-16P-4K	Dahua IP 16ch 16 PoE 1.5U Lite NVR 4K • Up to 16 channel IP camera input • H.265/H.264/MJPEG dual codec decoding • Max 256Mbps incoming bandwidth • Up to 8ch@1080P(4ch@H.265+4ch@H.264) realtime live-view • Up to 12Mp resolution live-view&playback • 2HDMI/1 VGA simultaneous video output • 16 channel synchronous realtime playback, GRID interface • ONVIF Version 2.4 conformance • 3D intelligent positioning with Dahua PTZ camera • Support 4 SATA HDDs up to 24TB, 3 USB(2 USB3.0), 1 eSATA port up to 16TB • Support IPC UPnP, 16PoE ports • Support P2P, QR code scan & add • Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & Smart Phone(DMSS)	
NVR 32 Channel			
RCDA313	NVR4232-8P-4K	Dahua IP 32ch 8 PoE 1U Lite NVR 4K • Up to 32 channel IP camera input • H.265/H.264/MJPEG dual codec decoding • Max 256Mbps incoming bandwidth • Up to 8ch@1080P(4ch@H.265+4ch@H.264) realtime live-view • Up to 12Mp resolution preview&playback • HDMI/VGA simultaneous video output • 8/16 channel synchronous realtime playback, GRID interface • ONVIF Version 2.4 conformance • 3D intelligent positioning with Dahua PTZ camera • Support 2 SATA HDDs up to 12TB, 2 USB(1 USB3.0) • Support IPC UPnP, 8PoE ports (for -8P model) • Support P2P, QR code scan & add • Multiple network monitoring: Web viewer, CMS(DSS/Smart PSS) & Smart Phone(DMSS)	
RCDA322	NVR5232-16P-4KS2	Dahua IP 32ch 16 PoE 1U Pro NVR 4K • H.265/H.264/MJPEG/MPEG4 codec decoding • Max 320Mbps incoming bandwidth • Up to 12Mp resolution preview&playback • HDMI/VGA simultaneous video output • 3D intelligent positioning with Dahua PTZ camera	
RCDA324	NVR608-32-4K	Dahua IP 32ch 2U Ultra NVR 4K • Intel Processor • Max 32 IP Camera Inputs • Max 384Mbps Incoming Bandwidth • Up to 12MP Resolution for Preview and Playback • Supports RAID 0/1/5/6/10/50/60 • iSCSI for Expanded Storage Space • Smart Tracking and Intelligent Video	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
NVR 64 Channel			
RCDA323	NVR5464-16P-4KS2	Dahua IP 64ch 16 PoE 1.5U Pro NVR • H.265/H.264/MJPEG/MPEG4 codec decoding • Max 320Mbps incoming bandwidth • Up to 12Mp resolution preview&playback • 2HDMI/VGA simultaneous video output • 3D intelligent positioning with Dahua PTZ camera	
NVR 128 Channel			
RCDA308	NVR6000DR	Dahua IP 128ch Super NVR • Max 128 channel IP cameras input with 1080P realtime live view • Max 384Mbps incoming bandwidth • Up to 64ch@1080P, 128ch@720P, 128ch@D1 realtime recording • Support 16 hot-swap SATA HDDs to better its scalability and flexibility • Support RAID 0/1/5 • Human-oriented Dahua UI • Compatible with Dahua SDK and seamless integrated to other platforms • ONVIF Version 2.2 conformance • Redundant power supply module adopted • Front LCD display	
NVR256 Channel			
RCDA309	NVR724DR-256	Dahua IP 256ch Super NVR • Max 256 channel IP cameras connection • Max 512Mbps incoming bandwidth • Up to 256ch@720P, 128ch@1080P, realtime recording • Support 24 hot-swap HDDs • Support RAID 0/1/5 • Support N+M hot standby • Support iSCSI & Mini SAS to expand storage space • Human-oriented Dahua UI • Compatible with Dahua SDK • ONVIF Version 2.2 conformance • Redundant power supply module adopted • Front LCD display	
DSS Managed Servers			
RCDA310	DH-DSS7016DR-M	Dahua Surveillance Management Center 2000 • Dahua DSS compact max support 200 input devices, support 2000 accounts management and 100 online users. • Embedded device, High-performance stream media transfer and storage capability • Support tier and cascade deployment • Support local storage and IP-SAN storage • Support GIS map(Google) • Support ONVIF, GB/T28181standard protocol gateway connection • Support platform SDK • Front panel displays system service status	
RCDA320	DSS4004-M	Dahua Surveillance Management Center 500 • DSS control command server embedded Linux OS supports 2000 channels, 500 Devices & 1000 users • Embedded device, 7*24 stable operation, client-server Architecture • High-performance stream media transfer and storage capability • Support distribute and cascade deployment • Support hot standby • Support local storage and IP-SAN storage • Support GIS map(Google, RasterMap) • Support ONVIF standard protocol connection • Support platform SDK • Support POS function • Support People Counting Statistic • Support VDP, through SIP Server • Support Heat Map • Support fisheye calibration in playback. • Support GIS Map. • Support to set up the devices, such as IPC, NVR, MDVR and so on • Support Yahoo, Gmail, Hotmail	

REDITRON CODE	MANUFACTURER CODE	ITEM DESCRIPTION	IMAGE
OTHER			
KBDA101	NKB1000	Dahua USB 3D keyboard controller - Keyboard to Control: -Dahua High Speed Dome (all models) -Dahua Standalone DVR -Dahua Network High Speed Dome -Network Video Server - Connections -RS485, RS422, USB, RS232 & Network - Three Dimensional Joystick Control of PTZ Functions - Preset Position, Auto Scan, Auto Pan, Auto Tour & Pattern Control - Auxiliary Functions - On-Screen Menu & User Operation Procedure Tips - Connect to SmartPSS via USB	
BRACKETS			
BRDA101-1	DH-PFB203W	Dahua Dome IP66 wall Mount - Material: Aluminum - Wall Mount Bracket - Neat & Integrated design	
BRDA107	DH-PFA122	Dahua IP66 Junction Box (3 lines) - Material: Aluminum - Wall Mount Bracket - Neat & Integrated design	
BRDA107-1	DH-PFA121	Dahua IP66 Junction Box (4 lines) - Material: Aluminum - IP66 Junction Box - Neat & Integrated design	
LENSES			
CLDA101	DH-PLZ1040-D	Dahua Lens 4MP 1/2.7" 2.7-12mm DC-Iris - Image format 1/2.7" - Focal length 2.7-12mm - Aperture F1.6 - Field Angle 1/2.7" W: 137.8°(D)x102.6°(H)x74.3°(V) ~T: 37.2°(D)x29.9°(H)x22.6°(V) 1/3" W: 120.1°(D)x91.3°(H)x66.3°(V) ~T: 33.9°(D)x27.1°(H)x20.3°(V) - M.O.D. 0.3m - TV Distortion -69.58%(W) ~-3.3% - IR Correction Yes - Lens Control - Focus Manual - Zoom Manual - Iris DC-Iris - Mount CS - Dimension Ø33.7x57.6mm - Weight 73.5g - Operating temperature -30 °C ~+70 °C 4 MegaPixel 2.7-12mm Lens	
CLDA102	DH-PLZ1140-D	Dahua Lens 4MP 1/2.7" 5-50mm DC-Iris - Image format - 1/2.7" - Focal length - 5-50mm - Lens pixel - 4MP - Aperture - F1.6 - Field Angle (D*H*V) 1/2.7" W: 70°(D)x50°(H)x37.5°(V)~T: 7°(D)x5.6°(H)x4.2°(V) 1/3" W: 52°(D)x41.6°(H)x31.2°(V)~T: 6.4°(D)x5.1°(H)x3.8°(V) - M.O.D. - 1m - TV Distortion - <15.1% - IR Correction - Yes - Focus Manual - Zoom Manual - Iris DC-Iris - Mount - CS - Dimension - Ø47x85.9mm - Weight - 195g - Operating temperature - -30°C +70°C - Humidity - <90% RH	
CONTROLLER			
ASDA102	PFM820	UTC Controller - Support different formats (HDCVI/AHD/HDTVI/CVBS) - Various format indicator lights, which makes it convenient for users to check the current format status and prompt if the format switch is successful.	

Codes: Product Codes - Reditron's Code to be used when Quoting or ordering product where applicable.

Abbreviations: - EOL - End of Life

*All prices are Retail excl. VAT. This pricelist replaces all prior pricelists and specials. E & OE. These prices are subject to fluctuations.

As such, prices will only be deemed as fixed once a written quotation is generated.

Quotations are valid for a period of 30 days and all quotations provided prior to this release will be upheld within the 30 day period.

CONTACT US



087 802 CCTV (2288)



sales@reditron.co.za



www.reditron.co.za



JOHANNESBURG (HEAD OFFICE)

18A, 5th Street, Sandton
Tel: 087 802 CCTV (2288)



CAPE TOWN

Unit 2, 7 Gold Street, Northgate Estate,
Maitland
Tel: 021 551 5841



DURBAN

Unit 9, 80 Rinaldo Road, Glen Anil
Tel: 031 263 1515



NELSPRUIT

Unit 4B, Waterfall Park,
17 Rapid Street, Riverside Industrial
Tel: 087 150 5517/8



PORT ELIZABETH

84 Pickering Street, Newton Park
Tel: 041 373 0395

